



## L.P. GAS CYLINDER INSTALLATION INSTRUCTIONS

### FORD FALCON /FAIRMONT/FAIRLANE SEDAN

#### EA, EB, ED, EF, EL, AU MODELS (1988 – 2002)

This Automotive LP Gas cylinder must be installed in the vehicle in strict accordance with the latest requirements of AS/NZS1425. Any modifications to the cylinder will render the warranty null and void.

#### GENERAL CYLINDER SPECIFICATIONS:

DIAMETER : 375MM	LENGTH: 860MM
CAPACITY : 85L (Water)	L.P GAS CAPACITY : 68L
VALVE ORIENTATION : 30 degrees.	

#### Installation:

This cylinder is designed to be mounted in the vehicle luggage compartment below the parcel shelf.



1. This cylinder is designed to be mounted in the luggage compartment, below the parcel shelf.



2. Remove the floor mat for the luggage compartment.



3. Lay down the back seats and place the cylinder into position ensuring the cylinder is not touching any part of the vehicle.



4. Mark the mounting holes with a permanent marker and remove the cylinder. Drill the holes where mark using a 13mm dia drill bit.



5. Place the cylinder into back into the vehicle using the bolts and washers supplied. Bolt down the vertical brackets first via the boot followed by the horizontal brackets via the back seat. Cut and re-fit boot mat to suit.