



L.P. GAS CYLINDER INSTALLATION INSTRUCTIONS

FORD FALCON / G6/ G6E FG SERIES

This Automotive LP Gas cylinder must be installed in the vehicle in strict accordance with the latest requirements of AS/NZS1425. Any modifications to the cylinder will render the warranty null and void.

GENERAL CYLINDER SPECIFICATIONS:

DIAMETERS : 330MM	LENGTH: 840MM
CAPACITY : 65L (Water)	L.P GAS CAPACITY : 52L
VALVE ORIENTATION : 30 degrees.	

This cylinder is designed to be mounted in the vehicle luggage compartment below the parcel shelf.



1. Remove the floor mat and side carpet mouldings. If the vehicle is a G6E model with Premium Sound System, cut the carpet from around the centre speaker.



2. Loosely bolt the attachment brackets onto the cylinder using the M10 x 30mm bolts, washers & Nyloc nuts supplied.



3. Place the cylinder into position ensuring no part of the cylinder is contacting the vehicle or carpet. Mark the location of the brackets. Remove the attachment brackets from the cylinder, line them up with the markings on the vehicle and mark out the hole locations. Cut the carpet to the shape of the attachment bracket.



4. Drill pilot holes where marked and using an 11mm dia drill, drill out the mounting holes.



5. Refit the carpet mouldings and bolt the cylinder into position using the 40 x 140mm backing plates supplied. Re-check the cylinder is not contacting the vehicle.