



L.P. GAS CYLINDER INSTALLATION INSTRUCTIONS

TOYOTA AURION / CAMRY SEDAN (2006 MODEL RELEASE)

This Automotive LP Gas cylinder must be installed in the vehicle in strict accordance with the latest requirements of AS/NZS1425. Any modifications to the cylinder will render the warranty null and void.

General Cylinder Specifications:

DIAMETER : 330mm	LENGTH : 850mm
COMBINED CAPACITY : 66L (Water)	L.P GAS CAPACITY : 63L
VALVE ORIENTATION : 75 degrees.	

Installation:



1). This cylinder is designed to be mounted in the luggage compartment, below the parcel shelf.



2). Remove the floor mat and carpet linings from the luggage compartment.



3). On the left side of the vehicle, tap smooth a pressed tab in the inner wheel arch.



4) Loosely fix the attachment brackets to the cylinder and position it in place ensuring the cylinder is not touching the vehicle at any point and the spare wheel can be accessed.



5). Mark the hole locations with a marker and drill them out using a 13mm drill bit.



6). Install the cylinder back into position. Tighten the attachment brackets to the cylinder.



7) Ensure square support washers fit are bent to fit the contour of the inner wheel arch.



8). Ensure the cylinder is mounted in tightly. Connect and test the cylinder in accordance with AS1425.